



Graver Technologies

FILTRATION | SEPARATION | PURIFICATION



QSL™ Series Filter Cartridges

*Serial Layered Design for
Optimized Prefiltration*

Product Specifications

Media: Polypropylene & Polyethersulfone

Inner core, end caps, cage: Polypropylene

Gaskets/O-Rings:

Buna-N, EPDM, Silicone, Teflon

Encapsulated Viton, Viton

Micron rating: 0.5

End styles: P (DOE), P2 (226/flat), P3 (222/flat), P7 (226/fin), P8 (222/fin), AM, NPC

Dimensions

Nominal lengths:

5", 9.75", 10", 19.5", 20", 29.25", 30", 39", 40"
(12.7, 24.8, 25.4, 49.5, 50.8, 74.3, 76.2, 99.1, 101.6 cm)

Outside diameter: 2.7" (6.86 cm)

Inside diameter: 1.0" (2.54 cm)

Surface Area: 7.0 ft² (0.65 m²)

Operating Parameters

Maximum operating temperature:
176°F (80°C)

Maximum differential pressure:
75 psid @ 70°F (5.2 bar @ 21°C)
30 psid @ 176°F (2.0 bar @ 80°C)

Maximum reverse pressure:
40 psid @ 70°F (2.8 bar @ 21°C)

Recommended change-out pressure:
35 psid (2.4 bar)

Incorporating a polypropylene microfiber media over a polyethersulfone membrane, the serial layered QSL cartridge design offers excellent retention characteristics and extended life to provide long lasting protection of downstream final filters. By preventing early blockage of downstream filters, the QSL contributes significantly to an economical overall design of your filtration system.

FEATURES & BENEFITS



- Serial layered design — enhances capacity and simplifies prefiltration requirements
- Absolute rated (99.98%) at 0.5 micron — acts as an ideal prefilter for 0.2 micron and 0.45 micron membrane filters
- Fixed pore construction — resists dirt unloading at maximum differential pressure
- High surface area — high flow rate, and long service life — minimize maintenance cost
- Available with various gasket/O-ring materials — compatible with many fluids

CERTIFICATIONS

- USP Class VI: Meets USP Class VI Biological Test for Plastics
- FDA Listed Materials: All materials comply with FDA Title 21 of the Code of Federal Regulations Sections 174.5, and 177.1520, as applicable for food and beverage contact.
- European Directive for Direct Food Contact: European Regulation No. 1935/2004 and European Regulation 10/2011: Tested for migration behavior and is suitable for contact with all kinds of foodstuffs with minimal rinse-up. Data available upon request.

TYPICAL APPLICATIONS

- Wine/beer bottling
- Aqueous solutions
- Culture Media
- Bottled water
- Active Intermediates
- Cosmetics
- Process water
- Diagnostic Reagents



PERFORMANCE SPECIFICATIONS

- **Cleaning/Sanitization:** Compatible with most common chemical cleaning, sanitizing and sterilizing agents and with pH range from 1–14. Consult factory for specific compatibility information. Cartridge will withstand hot water at 176°F (80°C) at 5 psid (0.35 bar) for 30 minutes.
- **Steam/Autoclave:** Cartridges may be autoclaved for 30 minutes at 250 °F (121°C) under no end load conditions. Cartridges fitted with steam insert may be steamed for at least 10 thirty minute cycles @ 275°F (135°C) not to exceed 3 psid (0.21 bar).


QSL NOMENCLATURE INFORMATION

Filter Type	Retention Rating (microns)	Nominal Length (inches)	End Configuration		Gasket or O-Ring	Options			
QSL Series	0.5	–5	–29.25	P	Double Open End	B	Buna-N	–R	Factory Rinse
		–9.75*	–30	P2	226/Flat Single Open End	E	EPDM		
		–10	–39	P3	222/Flat Single Open End	S	Silicone	–I	Steam Insert
		–19.5	–40	P7	226/Fin Single Open End	T	Teflon encap. Viton		
		–20		P8	222/Fin Single Open End	V	Viton		
				AM	Single Open End, Internal O-Ring				
Example: QSL 0.5–20P3S–I				NPC	Double Open End, Internal O-Ring				
QSL	0.5	–20		P3		S		–I	

*Available only for DOE (P) configuration

QSL FLOW RATE

Typical Flow Rate Clean Water at Ambient Temperature
(per 10" cartridge)



For liquids other than water, multiply pressure drop by the fluid viscosity in centipoise

FOR MORE INFORMATION

Customer Service/Technical Support: 1-888-353-0303
Europe (UK): +44-1424-777791 China: +86-21-5238-6576
Asia: +65 9671 9966

GTX-364 6-19



DISTRIBUTED BY

All information and recommendations appearing in this bulletin concerning the use of products described herein are based on tests believe to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Graver Technologies as to the effects of such use or the results to be obtained. Graver Technologies assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations. QSL is a trademark of Graver Technologies, LLC.



Graver Technologies | 200 Lake Drive, Glasgow, DE 19702 | 302-731-1700 | 800-249-1990
Fax: 1-302-369-0938 | info@gravertech.com | www.gravertech.com

A member of The Marmon Group—A Berkshire Hathaway Company